

Manual Swipe Magnetic Card Reader

Magnetic Digital Header TTL Interface – MH730A

Features

- TTL Interface. Clock and Data output.
- Low power consumption
- Operational power 2.7V ~ 5.5V DC
- Design for reading low and high coercivity 300 ~ 4000 Oe magnetic cards.
- Read Credit cards, Bank cards, Driver's licenses, and ID cards
- Interference-resistant against EAS signal.
- Customization available.



Application

- Magnetic stripe card reader.
- POS Keyboard.
- Security Control.
- CAT (Card Authorization Terminal).

Specification

- Power voltage: DC2.7V~5.5V
- Consumption: DC3.3V max. 3.2mA
DC5.0V max. 4.0mA
- Logic characteristic: default at Negative (positive optional)
- Card types: ISO, ANSI, AAMVA, CA DMV. (300~4000 Oe)
- Read speed range/second: 10 cm ~ 150 cm. (5 ips ~55 ips)
- Card thickness: 0.25mm ~ 1.2mm
- MTBF: electronics.. 100,000 hours..
Heads life: 500,000 passes under normal ideal Lab. environment
- Environment: Operating : -10°C ~ +55°C 10%~90% humidity.
Storage : -30°C ~ +70°C 100% humidity.

